



Advanced Reactive Drying

5931 Ford Court Brighton, MI 48116 • 810.229.7900
 Fax: 810.229.7908 • sales@cdims.com • cdims.com

MS-4800/4000-ARID-Dry Units

<u>Model</u>	<u>CFM</u>	<u>Fuel Type</u>	<u>Length</u>	<u>Width</u>	<u>Height</u>	<u>Weight</u>
CDH-RC-134	4,800/4,000*	Electric	94" **	43"	70"	1,600 lbs
CDH-RC-134	4,800/4000*	Gas	94" **	43"	70"	1,600 lbs

<u>Model</u>	<u>Moisture Removal Lbs/Hr 80°/60% RH</u>	<u>Moisture Removal Gallons/Day 80°/60% RH</u>	<u>Moisture Removal Lbs/Hr 55°/80% RH</u>	<u>Moisture Removal Gallons/Day 55°/80% RH</u>	<u>Moisture Removal Lbs/Hr 40°/80% RH</u>	<u>Moisture Removal Gallons/Day 40°/80% RH</u>
CDH-RC-134-E	102	295	87	251	56	161
CDH-RC-134-G	102	295	87	251	56	161

<u>Pipe Size</u>	<u>LP Inlet Pressure</u>	<u>Natural Gas Inlet Pressure</u>	<u>Electric Reactivation Load 230/1/60</u>	<u>Electric Reactivation FLA Load 460/3/60</u>	<u>Gas Reactivation FLA Load 230/1/60</u>	<u>CFH Gas Max Usage NG</u>	<u>Gallon/HR Max Usage LP</u>
N/A	N/A	N/A	N/A	104	N/A	N/A	N/A
½"	7-14" w.c.	7-14" w.c.	N/A	N/A	45	320	3.2



Available Accessories:

- Remote Humidistat
- Cooling Coil Modules
- Heating Coil Modules
- Trailer Mounting
- 18" or 20" Round Connections
- Ductwork and layflat
- **Casters and brackets -add 12" to length